

LOCATION MAP
SCALE: 1"=600'

BENCH MARK
TOP OF FOUNDATION
AT CORNER
ELEV. = 76.0 (M.S.L.)

APPROXIMATE EDGE OF 100
YEAR FLOOD HAZARD ZONE
TAKEN FROM THE FLOOD
INSURANCE RATE MAP (FIRM)
FOR THE TOWN OF SEEKONK
COMMUNITY PANEL NO. Z50063 00054A
DATED SEPTEMBER 5, 1974

- EROSION AND SEDIMENTATION CONTROL**
- 1) ALL PERIMETER EROSION AND SEDIMENTATION CONTROLS MUST BE INSTALLED PRIOR TO THE COMMENCEMENT OF EARTHWORK.
 - 2) ACCESSIBLE RESERVES OF HAY BALES AND STAKES ARE TO BE MAINTAINED ON SITE FOR ROUTINE MAINTENANCE AND IN THE EVENT OF UNANTICIPATED PROBLEMS REQUIRING EMERGENCY RESPONSE.
 - 3) HAY BALES SHOULD BE INSTALLED IN ACCORDANCE WITH THE DETAILS PROVIDED.
 - 4) NO WORK IS TO OCCUR ON THE WETLAND SIDE OF THE PERIMETER EROSION AND SEDIMENTATION CONTROLS. ALL PERIMETER CONTROLS SERVE AS THE PROJECT LIMIT OF DISTURBANCE.
 - 5) NO STONES, BRUSH, CONSTRUCTION DEBRIS, LITTER, OR OTHER MATERIALS ARE TO BE DEPOSITED ON THE WETLAND SIDE OF THE EROSION AND SEDIMENTATION CONTROLS.
 - 6) ALL DISTURBED SOILS NOT DESIGNATED FOR OTHER SURFACE TREATMENT ARE TO BE LOAMED AND SEEDED IMMEDIATELY FOLLOWING FINAL GRADING.
 - 7) EXISTING LAWN AREAS TO BE MAINTAINED AS SHOWN.
 - 8) APPROPRIATE PRECAUTIONS SHOULD BE TAKEN TO PREVENT THE TRANSPORT OF SOIL OFF SITE FROM CONSTRUCTION EQUIPMENT.
 - 9) ALL PERIMETER EROSION AND SEDIMENTATION CONTROLS MUST BE PROPERLY MAINTAINED AND MUST REMAIN IN PLACE UNTIL THE SOILS HAVE BEEN STABILIZED TO THE SATISFACTION OF THE ENGINEER AND THE SEEKONK CONSERVATION COMMISSION.

NOTE:
CONTACT DIKE ENERGY TO OBTAIN STANDBY PERSONNEL FOR WORK ADJACENT TO PIPELINE. WESTHOOD OFFICE PHONE #781-324-3750 - JACK DORAN. DIGHTON OFFICE PHONE #508-664-5471 - DENNIS MAYNARD.



LEGEND
--- EXISTING CONTOUR
--- PROPOSED CONTOUR
--- TREE

Received
SEP 23 2002
Con. Comm.

PLAT 22
LOT 40
RECORD LOT NO. 3
AREA = 7.614 ACRES
OWNER:
KENNETH H. AND SANDRA PROVOST
303 WOODWARD AVENUE
SEEKONK, MA. 02771
ZONE: R-4 69-505

PROPOSED HORSE BARN
303 WOODWARD AVENUE
SEEKONK, MASSACHUSETTS

CAPUTO AND WICK LTD. DATE: AUGUST 28, 2002
1150 PAWTUCKET AVE. RUMFORD, R.I. 02916 SHEET 1 OF 1
401-434-8880



- NOTES:**
1. UNDESIRABLE SOILS SHOULD BE REMOVED AND THE TRENCH AFTER INSTALLATION OF TRENCH CONTROL DEVICES.
 2. SILT FENCE FABRIC SHALL NOT BE SLEET AND THE POLES ARE NOT TO BE SPACED MORE THAN 10 FEET APART.
 3. PILES OF SOIL SHOULD BE 10 FEET HIGH. PILES SHOULD BE LOCATED ON DOWNWIND SIDE OF WETLAND AREA AND NOT ALLOWED TO BE A WIND-DRIVEN BALLY UNDER A GULF OF WIND AS SHOWN ON THE PLAN.

PLAN
SCALE: 1"=30'

HAY BALE DETAIL

SILT FENCE